ASHE CONTROLS PVT LTD
an ISO 9001:2015 certified company

TX-232

TX-Series Signal Isolating Repeater



RoHS Compliant CE MAKE IN INDIA Modbus

Overview

The ASHE TX series of Signal Conditioners, Isolators, Transducers, Transmitters and Multipliers comprise a wide range of high quality and reliable instruments for the conversion, amplification, isolation and multiplication of analog and digital signals.

The instruments accept standard industrial process input signals such as DC/AC Voltage, DC/AC Current, 4 to 20 mA DC, RTD Pt-100 sensor, Thermocouple sensor, Frequency [Pulse], Resistance etc. and provide buffered and isolated outputs with enhanced load driving capacity. Additionally, the TX Series Transducers optionally can provide the input process signal on RS485 Modbus RTU. The instruments find wide usage in single loop or distributed process measurement and control applications.

The new Series TX-232 Signal Isolating Multipliers measure an analog signal and convert the signal into two (or more) isolated analog signals of 4 to 20 mA DC [or as required]. The Output signals are linear with respect to the Input signal and each output is galvanically and optically isolated to a level of 3 kV rms for one minute. An RS485 signal can also be provided at the terminals for data communication.

The instruments operate on Universal AC or DC power supply. Optional features include higher load driving capability, digital indication facility, two-wire operation with auxillary power output, etc.

The instruments are available in slim & compact industrial grade enclosures in DIN Rail / Wall-mounting execution, or optionally in IP66 protected field mount weather-proof enclosures, or in Ex-d certified explosion-proof enclosures. Absence of any moving parts provides these instruments inherent advantages like immunity to mechanical shocks, dust, ambient temperature, humidity and corrosive atmosphere.

This product is backed by a full two-year warranty, covering all manufacturing defects and workmanship issues under normal operating conditions.

Specifications


Model	ASHE TX-232.
Type	Analog Signal Isolating Multiplier (Repeater / Splitter).
Principle	Optical Isolation, Signal Conditioning and Amplification.
Input Signal	4 to 20 mA DC [or as required].
Output Signals	Two isolated and buffered outputs of 4 to 20 mA DC [or as required] .
Load Driving Capacity	600 Ohms for each output.
Communication	RS485 on Modbus RTU communication (optional) to be specified.
Linearity	± 0.1%.
Isolation	Between Input // Outputs // Power Supply.
Isolation Type	Optical and Galvanic.
Isolation Level	3 kV RMS for one minute.
Output Protection	Short / Open Circuit protection.
Calibration Facility	Zero and Span settings [external].
Accuracy	± 0.1%.
Indication	Red LED for Power On.
Power Supply	90 to 270 VAC, 50/60 Hz Universal AC/DC Power supply [Optionally 20 to 70 V DC].
Dimensions	100 x 22 x 110 mm. [H x W x D].
Execution	DIN-Rail / Rear panel mounting.
Enclosure	Industrial grade ABS.
Weight	Approximately 0.4 kg.
Operating Temperature	0 to 55^{0}C.

Features


- Optical & Galvanic Isolation between Input, Outputs & Power Supply
- High accuracy and linearity to input signal
- Very low power consumption and heat dissipation
- Options of multiple [upto four] isolated outputs (we offered in other enclosure)
- High load driving capacity of retransmitted signal
- RS485 on Modbus RTU output option (to be specified)
- Output signal options of current / voltage
- Short-circuit / Open-circuit protection of outputs
- Front accessible Zero and Span calibration for all channels
- Rugged, industrial grade ABS enclosure
- Panel / Field / Hazardous area installation in IP66 execution
- Current limiting for I/O protection
- Customized outputs offered
- Two-year Performance Warranty
- Proven track record of successful site installations

TX-Series Signal Isolating Repeater

Block Diagram



Dimensional Diagram



FRONT VIEW SIDE VIEW

How To Order

	SIGNAL ISOLATING REPEATER (dual channel)	**TX-232-**				
	Configuration and add-on options					
1	**POWER SUPPLY**					
▸	AC Voltage 90 to 270 VAC, 50 Hz		A			
▸	DC Voltage 20 to 70 VDC		D			
2	**INPUT SIGNAL**					
▸	DC Current			L		
▸	DC Voltage			V		
▸	AC Voltage			A		
3	**OUTPUT SIGNAL**					
▸	DC Current				L	
▸	DC Voltage				V	
4.	**COMMUNICATION**					
▸	RS485 Modbus RTU required (not for AC Voltage Input)					M
▸	Rs485 Modbus RTU Not required					N

Our Other Products


FLOW TOTALIZER


SIGNAL ISOLATORS & TRANSDUCERS


TEMPERATURE SCANNER


FLAMEPROOF INSTRUMENTS


STATIC POWER SWITCHES

ASHE CONTROLS PVT LTD
an ISO 9001:2015 certified company

Designed and Manufactured by :
ASHE CONTROLS PRIVATE LIMITED
6/317, 318 & 319, Jogani Industrial Complex, Near ATI, Sion-Trombay Road, Chunabhatti (East), Mumbai - 400 022, India.
Phone : (022) 2405 1561, 2405 5791, 2405 5543 • E-mail : sales@ashecontrols.com • Website: http://www.ashecontrols.com